MURR ELEKTRONIK
stay connected

Reset button with 2 illuminated push buttons

Every 1 NO contact in a IP65 enclosure


Art.No.: 69012
Weight: 0.115 kg
Country of origin: DE
Model designation: R-Button 42 2NO L M12(8)


R-Button / 42 2NO L M12(8)
with M12 connection
8-pole
2 buttons can be lit (each 1 NO contact)
Delivery contents:
Flat lens, transparent clear, red, yellow, green, blue
Label plates, O, I, R, ↑,↓
mounting with clip on the back side


[Link to Product]

Illustration









Product may differ from Image

Commercial data

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-04-30

MURR ELEKTRONIK
stay connected

URL Webshop	https://shop.murrelektronik.com/69012
GTIN	4048879594325
Customs tariff number	85365080
ECLASS-6.0	27371228
ECLASS-6.1	27371228
ECLASS-7.0	27371228
ECLASS-7.1	27371228
ECLASS-8.0	27371228
ECLASS-8.1	27371228
ECLASS-9.0	27371228
ECLASS-9.1	27371228
ECLASS-10.0.1	27371228
ECLASS-10.1	27371228
ECLASS-11.0	27371228
ECLASS-11.1	27371228
ECLASS-12.0	27371228
ECLASS-13.0	27371228
ECLASS-14.0	27371228
ETIM-5.0	EC000225
ETIM-6.0	EC000225
ETIM-7.0	EC000225
ETIM-8.0	EC000225
customs tariff number	85365080
EAN	4048879594325
Packaging unit	1
Electrical data	
Operating voltage AC/DC LED illumination max.	30 V
Operating current LED illumination	14 mA @ 24 V DC
Electrical data | Supply	
Operating voltage DC min.	1 V
Operating voltage DC max.	36 V
Operating current	1,5 A
Operating voltage DC (UL Recognized)	30 V
Device protection	
Condition lifetime	load-dependent, temperature dependent
Device protection | Electrical	
Degree of protection (EN IEC 60529)	IP65
Electrical lifetime	0 cycles
Device protection | Mechanical	
Mechanical endurance	0 cycles
Mechanical data	
Bounce time max.	10 ms
Mechanical data | Material data	
Material contact	AgNi
Mechanical data | Mounting data	
Height	29 mm
Width	124 mm
Depth	42 mm
Environmental characteristics | Climatic	
Operating temperature min.	-25 °C

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-04-30

Operating temperature max.	70 °C
Ambient temperature (storage, transport)	-25 °C … 85 °C
Connection type 1	
Family construction form	M12
No. of poles	8
Coding	A
Gender	male
Color contact carrier	black
PIN 1	NO 1
PIN 2	NO 1
PIN 3	X 2 -
PIN 4	X 1 +
PIN 5	NO 2
PIN 6	NO 2
PIN 7	X 2 -
PIN 8	X 1 +

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-04-30